AKURATE DYNAMICS

AKURATEDYNAMICS.COM | INFO@AKURATEDYNAMICS.COM | (832) 672-5665

DELTA CPS-HV
PROPORTIONER

- Individual gear pump driven system with integrated software to independently adjust motor speeds
- High resolution flow meters analyze thousands of data points to create seamless adjustments to chemical flow
- Intuive system dynamically adjusts to automatically ensures on-ratio application everytime

SPECIFICATIONS

APPLICATION	Medium to High Volume - Wall Foam, Roofing, Polyurea
POWER INPUT	Nominal 200-240 VAC, 1 Phase or 3 Phase, 50/60 HZ
WEIGHT	500 lbs
DIMENSIONS	36” (Width) X 28” (depth) X 52” (Height)
OPERATING TEMP	50 - 130 Degrees Fahrenheit
MAX FLUID WORKING PRESSURE	2000 PSI, 3000 PSI Polyurea
MAX FLUID TEMP	150 Degrees Fahrenheit
POWER BUDGET ELECTRIC HEAT	10.5 kW
HMI	TFT - LCD with Touch Screen
HOSE ELECTRICAL CODE	GFI Protected Hoses
MAX HOSE LENGTH	400’
ALARMS	Descriptive Alarms with Time Stamp